

PRIMA PREMIUM 15W-40 CK-4

Premium Tractor Engine Oil

Product Description

Veedol Prima Premium 15W-40 CK-4, a premium engine oil formulated to meet the requirement of all farm tractors meeting the latest TREM Stage-V emission norms. Engineered to deliver exceptional oxidation stability, wear protection, and resistance to oil breakdown, this premium lubricant ensures engine cleanliness and longevity. Also suitable for tractors meeting older emission norms.

Ideal for severe operating conditions, this advanced synthetic blend oil combined with latest additive technology, provides unmatched protection for engines equipped with Exhaust Gas Recirculation (EGR), Diesel Particulate Filters (DPF), and Selective Catalytic Reduction (SCR) emission control technologies.

Performance Specifications:

Veedol PRIMA PREMIUM 15W-40 CK-4 meets & exceeds the performance requirements of

- API CK-4, CJ-4, CI-4 Plus

Application:

- Suitable for farm tractors of lower and higher horsepower (HP), manufactured by different OEMs meeting the latest TREM Stage-V emission norms.
- Also suitable for all tractors and farm machineries meeting TREM Stage-IV and older emission norms.
- Recommended oil drain interval 1200Hours*

Features/Benefits:

- **Excellent engine cleanliness:** High resistance to sludge formation, oil thickening, and deposit control ensure a cleaner engine throughout the recommended oil drain period.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

- **Unmatched protection:** Advanced additive technology provides outstanding wear protection under high load conditions. Also protects exhaust gas treatment systems fitted in tractors meeting TREM-V norms due to Low-SAPS content.
- **Exceptional performance:** Robust thermal and oxidation resistance ensures trouble free operation during longer oil drain period.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Density @ 29.5°C	cSt	D 4052	0.8600
Kinematic Viscosity @ 40°C	cSt	D 445	102.3
Kinematic Viscosity @ 100°C	cSt	D 445	14.50
Viscosity Index		D 2270	146
Flash Point	°C	D 92	248
Pour Point	°C	D 927	-33
Total Base Number	mgKOH/g	D 2896	7.6

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.