



Prima Premium 15W-40 CK-4

Premium Multigrade Tractor Engine Oil
Advanced synthetic blend

PRODUCT DATA SHEET

Product Description:

Veedol Prima Premium 15W-40 CK-4, a premium engine oil formulated to meet the requirement of all farm tractors meeting the latest TREM Stage-V emission norms. Engineered to deliver exceptional oxidation stability, wear protection, and resistance to oil breakdown, this premium lubricant ensures engine cleanliness and longevity. Also suitable for tractors meeting older emission norms.

Ideal for severe operating conditions, this advanced synthetic blend oil combined with latest additive technology, provides unmatched protection for engines equipped with Exhaust Gas Recirculation (EGR), Diesel Particulate Filters (DPF), and Selective Catalytic Reduction (SCR) emission control technologies.

Performance Specification:

Veedol Prima Premium 15W-40 CK-4 meets and exceeds below performances

API CK-4, CJ-4, CI-4 Plus, CH-4

Features/Benefits:

- **Excellent engine cleanliness:** High resistance to sludge formation, oil thickening, and deposit control ensure a cleaner engine throughout the recommended oil drain period.
- **Unmatched protection:** Advanced additive technology provides outstanding wear protection under high load conditions. Also protects exhaust gas treatment systems fitted in tractors meeting TREM-V norms due to Low-SAPS content.
- **Exceptional performance:** Robust thermal and oxidation resistance ensures trouble free operation during longer oil drain period.

Application:

- Suitable for farm tractors of lower and higher horsepower (HP), manufactured by different OEMs meeting the latest TREM Stage-V emission norms.
- Also suitable for all tractors and farm machineries meeting TREM Stage-IV and older emission norms.
- Recommended oil drain interval 1200Hours*

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.860
Kinematic Viscosity @ 40°C, cSt	ASTM D445	102.3
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.50
Viscosity Index	ASTM D2270	146
Flash Point (COC), °C	ASTM D92	248
Pour Point, °C	ASTM D97	-33
Total Base Number, mg KOH/g	ASTM D2896	7.6

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:
The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

* Oil drain period recommended above is under standard test conditions. It may vary based on actual driving and vehicle condition. Please refer to the vehicle service manual for oil specification and drain interval for specific vehicle types.