



Take-Off 4S Premium Scooter 5W-30 SP / MB

Premium Four Stroke Gearless Scooter Engine Oil  
Advanced Synthetic Blend

PRODUCT DATA SHEET

Product Description:

Veedol Take-Off 4S Premium Scooter 5W-30 SP / MB, a premium engine oil meeting the latest JASO specification, is specifically designed for gearless scooters. The advanced synthetic blend fortified with scooter-specific additives helps maintain a cleaner engine and improves efficiency in modern scooter engines. With its low viscosity, this oil delivers instant cold start and enhances fuel efficiency ensuring optimal performance.

Veedol Take-Off 4S Premium Scooter 5W-30 SP / MB ensures unmatched protection, excellent thermal stability, and outstanding oxidation resistance, keeping the engine running smoothly under all conditions.

Performance Specification:

Veedol Take-Off 4S Premium Scooter 5W-30 SP / MB meets and exceeds below performances

API SP

JASO MB T903: 2023

Features/Benefits:

- Unmatched protection:** High performance additives protect highly stressed engine components from sludge, corrosion, deposits, and wear, leading to reduced maintenance costs.
- Reduced friction and improved fuel economy:** The latest friction modifiers minimize internal friction, enhances engine efficiency, and improves fuel economy, ensuring a smoother ride.
- Advanced synthetic technology:** The advanced synthetic blend offers enhanced performance, and extended oil life for optimal scooter operation.

Application:

- Recommended for modern scooters fitted with automatic transmissions and dry clutch.
- Suitable for air and water-cooled four stroke engines with automatic transmission.

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.851
Kinematic Viscosity @ 40°C, cSt	ASTM D445	63.50
Kinematic Viscosity @ 100°C, cSt	ASTM D445	10.80
Viscosity Index	ASTM D2270	161
Flash Point (COC), °C	ASTM D92	238
Pour Point, °C	ASTM D97	-39
Total Base Number, mg KOH/g	ASTM D2896	7.1

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:  
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:  
The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.