



Product Description:

Veedol Trac One Premium, a top tier “Universal Tractor Transmission Oil” (UTTO), designed to meet the diverse needs of modern agricultural machinery and off-road equipment. An advanced synthetic blend, this premium oil ensures exceptional protection and performance for transmissions, hydraulic systems, and oil immersed brakes (wet brakes).

Veedol Trac One Premium offers unmatched wear protection, excellent thermal stability, and reliable friction control, enabling smooth and efficient operation of equipment in demanding environments. It delivers unmatched performance, extended equipment life, and reduced maintenance costs, keeping your machinery running at peak efficiency.

Performance Specification:

Veedol Trac One Premium meets and exceeds below performance

API GL-4	John Deere JDM J20C	Same Deutz Fahr Transmission
Allison C-4	Massey Ferguson CMS 1143	Caterpillar CAT TO-2
	Case New Holland CNH 3509	Case MS 1205

Features/Benefits:

- **Unmatched protection:** Excellent anti-wear, anti-corrosion, and anti-foaming characteristics resulting from use of latest additive technology leading to greater reliability and reduced downtime. Thus, minimizing maintenance cost and maximizing utilization.
- **High oxidation resistance:** Advanced additives offer excellent oxidation and corrosion resistance, keeping transmission system clean and efficient by preventing harmful deposits and rust.
- **Unmatched wet brake performance and chatter free operation:** Advanced synthetic blend oil fortified with robust additive offers exceptional friction control, minimizing brake chatter and ensuring smooth, consistent braking performance.

Application:

- Suitable for use in a wide range of agricultural equipment, including tractors, combine harvesters, and other farm machinery.
- Also recommended for heavy-duty transmissions, differentials, final drives, hydraulic systems, wet brakes, power take-offs and hydrostatic drives of off-highway and construction machinery.

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.853
Kinematic Viscosity @ 40°C, cSt	ASTM D445	59.6
Kinematic Viscosity @ 100°C, cSt	ASTM D445	10.07
Viscosity Index	ASTM D2270	156
Flash Point (COC), °C	ASTM D92	248
Pour Point, °C	ASTM D97	-42
CCS Viscosity @ -25°C, cP	ASTM D5293	4386
Brookfield Viscosity @ -35°C	ASTM D2963	46700

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:
The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.