



Heavy Pull Premium 15W-40 CI-4 Plus

Premium Small Commercial Vehicle Engine Oil
Advanced synthetic blend

PRODUCT DATA SHEET

Product Description:

Veedol Heavy Pull Premium 15W-40 CI-4 Plus is a high-quality diesel engine oil formulated with advanced performance additives to deliver unmatched performance in small commercial vehicles operating in harsh conditions and stop-and-go traffic.

The advanced synthetic blend offers excellent viscosity and soot control providing extended drain capability and long life. It offers outstanding protection against wear for light-duty diesel engines operating under a wide variety of service conditions.

Performance Specification:

Veedol Heavy Pull Premium 15W-40 CI-4 Plus meets and exceeds below performance

API CI-4 Plus

Features/Benefits:

- **Unmatched protection:** Exceptional additive system provides outstanding wear protection characteristics under severe operating conditions, enhancing engine life.
- **Excellent oxidation resistance:** High resistance to oxidation prevents sludge formation, oil thickening, and deposit control ensuring a cleaner engine throughout the recommended oil drain period.
- **Trouble free operation during long drain service intervals:** Advanced synthetic blend resists thermal degradation of engine oil ensuring trouble free operation during longer oil drain period.

Application:

- Small commercial vehicles of various manufacturers meeting BS IV emission norms.
- Pickup trucks, Minivans, Minibus, Utility vehicles, etc.

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.862
Kinematic Viscosity @ 40°C, cSt	ASTM D445	102.3
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.50
Viscosity Index	ASTM D2270	146
Flash Point (COC), °C	ASTM D92	248
Pour Point, °C	ASTM D97	-30
Total Base Number, mg KOH/g	ASTM D2896	7.2

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:
The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.