



Prima Premium 15W-40 CI-4 Plus

Premium Multigrade Tractor Engine Oil
Advanced synthetic blend

PRODUCT DATA SHEET

Product Description:

Veedol Prima Premium 15W-40 CI-4 Plus is an advanced diesel engine oil formulated with high-performance additives to deliver excellent performance in modern tractor engines meeting TREM-IV emission norms.

The advanced synthetic blend offers long life and extended drain capability, providing excellent viscosity and soot control. It offers outstanding protection against wear for tractor engines operating under a wide variety of service conditions.

Performance Specification:

Veedol Prima Premium 15W-40 CI-4 Plus meets and exceeds below performances

API CI-4 Plus

Features/Benefits:

- **Unmatched protection:** Exceptional additive system provides outstanding wear protection characteristics.
- **Excellent engine cleanliness:** High resistance to sludge formation, oil thickening, and deposit control ensure a cleaner engine throughout the recommended oil drain period.
- **Longer engine life and drain service intervals:** Advanced synthetic blend and unique performance additives resist thermal and oxidation degradation, ensuring proper lubrication that provides longer engine life and extended oil drain intervals.

Application:

- Tractors manufactured by various Indian and international OEMs that meet TREM-IV emission norms.
- Suitable for older generation tractors, combined harvesters, and other farm equipment engines.
- Recommended oil drain interval 1000 hours*

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.862
Kinematic Viscosity @ 40°C, cSt	ASTM D445	102.3
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.50
Viscosity Index	ASTM D2270	146
Flash Point (COC), °C	ASTM D92	248
Pour Point, °C	ASTM D97	-30
Total Base Number, mg KOH/g	ASTM D2896	7.2

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

* Oil drain period recommended above is under standard test conditions. It may vary based on actual driving and vehicle condition. Please refer to the vehicle service manual for oil specification and drain interval for specific vehicle types.