

PRIMA-PRO 15W-40 CI-4

Tractor Engine Oil

Product Description

Veedol Prima Pro 15W-40 CI-4 is a high-quality engine oil formulated with the finest base oils and advanced additives to deliver superior performance in tractors.

The synthetic blend ensures a prolonged service life and extended drain intervals, offering excellent control over viscosity and soot buildup. It provides superior protection against wear and maintains stability at both low and high temperatures under varying operating conditions.

Performance Specifications:

Veedol PRIMA PRO 15W-40 CI-4 meets & exceeds the performance requirements of

- API CI-4

Application:

- Suitable for all tractors manufactured by Indian and international OEMs complying with TREM-III A or TREM-IV emission norms.
- Also be used in construction equipment & DG sets.
- Recommended oil drain interval 600 hours*

Features/Benefits:

- **Superior protection:** High performance additive system provides very good wear protection to pistons, rings, cylinder liner, and valve train.
- **Superior viscosity control:** Special synthetic blend provides superior viscosity control, resisting thermal and oxidation degradation.
- **Improved engine cleanliness:** Superior resistance to sludge formation, oil thickening, and deposit control ensure a cleaner engine throughout the recommended oil drain period.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Density @ 29.5°C	cSt	D 4052	0.8650
Kinematic Viscosity @ 40°C	cSt	D 445	108.2
Kinematic Viscosity @ 100°C	cSt	D 445	15.12
Viscosity Index		D 2270	146
Flash Point	°C	D 92	244
Pour Point	°C	D 927	-33
Total Base Number	mgKOH/g	D 2896	8.4

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

VEEDOL CORPORATION LIMITED

[formerly Tide Water Oil Co. (India) Limited]

Corporate Office: 902, Godrej TWO, Vikhroli, Eastern Express Highway, Mumbai-400 079.

Regd. Office: Yule house, 8, Dr. Rajendra Prasad Sarani, Kolkata-700 001, West Bengal, India.

www.veedolindia.com