



Prima Pro 15W-40 CI-4

Multigrade Tractor Engine Oil

Synthetic blend

PRODUCT DATA SHEET

Product Description:

Veedol Prima Pro 15W-40 CI-4 is a high-quality engine oil formulated with the finest base oils and advanced additives to deliver superior performance in tractors.

The synthetic blend ensures a prolonged service life and extended drain intervals, offering excellent control over viscosity and soot buildup. It provides superior protection against wear and maintains stability at both low and high temperatures under varying operating conditions.

Performance Specification:

Veedol Prima Pro 15W-40 CI-4 meets and exceeds below performance

API CI-4

Features/Benefits:

- **Superior protection:** High performance additive system provides superior wear protection to pistons, rings, cylinder liner, and valve train.
- **Improved engine cleanliness:** Superior resistance to sludge formation, oil thickening, and deposit control ensure a cleaner engine throughout the recommended oil drain period.
- **Superior viscosity control:** Special synthetic blend provides superior viscosity control, resisting thermal and oxidation degradation.

Application:

- Suitable for all tractors manufactured by Indian and international OEMs complying with TREM-III A or TREM-IV emission norms.
- Also be used in construction equipment & DG sets.
- Recommended oil drain interval 600 hours*

Typical Properties:

| Parameters | Test Method | Results |
|----------------------------------|-------------|---------|
| Density @ 29.5°C | ASTM D4052 | 0.865 |
| Kinematic Viscosity @ 40°C, cSt | ASTM D445 | 108.28 |
| Kinematic Viscosity @ 100°C, cSt | ASTM D445 | 15.12 |
| Viscosity Index | ASTM D2270 | 146 |
| Flash Point (COC), °C | ASTM D92 | 244 |
| Pour Point, °C | ASTM D97 | -33 |
| Total Base Number, mg KOH/g | ASTM D2896 | 8.4 |

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:
The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

* Oil drain period recommended above is under standard test conditions. It may vary based on actual driving and vehicle condition. Please refer to the vehicle service manual for oil specification and drain interval for specific vehicle types.