

## Veedol TRAC ONE ECO

### Multi-functional Tractor Transmission and Hydraulic Oil

#### Product Description:

Veedol Trac One Eco 80W GL-4, is a universal tractor transmission oil specially formulated with highly refined base oil and robust additive technology. It offers reliable clutch performance, reduced brake chatter, assured wear protection & load carrying capability thus reducing maintenance costs.

Veedol Trac One Eco 80W GL-4 is designed to optimize the performance of agricultural and commercial tractors operating in a wide range of environments and conditions.

#### Performance Specifications:

Veedol TRAC ONE ECO meets and exceeds below performances

- API GL-4

#### Application:

- Recommended for agricultural tractors, off-highway, and mining equipment with common sump for transmission, hydraulics, power steering, and oil immersed brakes.
- Heavy-duty transmissions, differentials, final drives, hydraulic systems, wet brakes, power take-offs and hydrostatic drives of off-highway and construction machinery.

#### Features/Benefits:

- **Assured protection:** Very good anti-wear, anti-corrosion, and anti-foaming characteristics ensure greater reliability and reduced downtime.
- **Reduced brake chatter:** Special additives in the formulation provide improved braking with reduced brake noise.
- **Longer transmission life:** Superior water tolerance coupled with enhanced extreme pressure characteristics provide longer transmission life, thereby reducing maintenance costs.



#### STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



#### HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

**Typical Properties:**

| Test Parameters              | Unit     | ASTM Test Method | Typical results |
|------------------------------|----------|------------------|-----------------|
| Density @ 29.5°C             | cSt      | D 4052           | 0.8650          |
| Kinematic Viscosity @ 40°C   | cSt      | D 445            | 87.83           |
| Kinematic Viscosity @ 100°C  | cSt      | D 445            | 11.19           |
| Viscosity Index              |          | D 2270           | 114             |
| Flash Point                  | °C       | D 92             | 248             |
| Pour Point                   | °C       | D 927            | -33             |
| Total Base Number            | mg/KoH/g | D 2896           | 5.1             |
| Brookfield Viscosity @ -35°C | cP       | D 2963           | 25500           |

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.


**STORAGE**

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.


**HEALTH, SAFETY AND ENVIRONMENT**

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

**VEEDOL CORPORATION LIMITED**

*[formerly Tide Water Oil Co. (India) Limited]*

Corporate Office: 902, Godrej TWO, Vikhroli, Eastern Express Highway, Mumbai-400 079.

Regd. Office: Yule house, 8, Dr. Rajendra Prasad Sarani, Kolkata-700 001, West Bengal, India.

[www.veedolindia.com](http://www.veedolindia.com)