



PRODUCT DATA SHEET

Product Description:

Veedol Trac One Eco 80W GL-4, is a universal tractor transmission oil specially formulated with highly refined base oil and robust additive technology. It offers reliable clutch performance, reduced brake chatter, assured wear protection & load carrying capability thus reducing maintenance costs.

Veedol Trac One Eco 80W GL-4 is designed to optimize the performance of agricultural and commercial tractors operating in a wide range of environments and conditions.

Performance Specification:

Veedol Trac One Eco 80W GL-4 meets below performance

API GL-4

John Deere JDM J20C

Features/Benefits:

- **Assured protection:** Very good anti-wear, anti-corrosion, and anti-foaming characteristics ensure greater reliability and reduced downtime.
- **Reduced brake chatter:** Special additives in the formulation provide improved braking with reduced brake noise.
- **Longer transmission life:** Superior water tolerance coupled with enhanced extreme pressure characteristics provide longer transmission life, thereby reducing maintenance costs.

Application:

- Agriculture tractors produced by various manufacturers.
- Transmissions, differentials, final drives, hydraulic systems, wet brakes, power take-offs and hydrostatic drives of off-highway and construction machinery.

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.865
Kinematic Viscosity @ 40°C, cSt	ASTM D445	87.83
Kinematic Viscosity @ 100°C, cSt	ASTM D445	11.19
Viscosity Index	ASTM D2270	114
Flash Point (COC), °C	ASTM D92	248
Pour Point, °C	ASTM D97	-33
Total Base Number, mg KOH/g	ASTM D2896	5.1
Brookfield Viscosity @ -26°C, cP	ASTM D2963	25500

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:
The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.