



Heavy Pull Pro 15W-40 CH-4

High Performance Small Commercial Vehicle Engine Oil

Synthetic blend

PRODUCT DATA SHEET

Product Description:

Veedol Heavy Pull Pro 15W-40 CH-4 is a diesel engine oil formulated with high-performance additives to deliver superior performance in various small commercial vehicles.

The synthetic blend, enhanced with balanced performance additives, helps maintain viscosity for longer durations, providing extended drain capability. It offers superior protection against wear, deposits, and ensures engine cleanliness.

Performance Specification:

Veedol Heavy Pull Pro 15W-40 CH-4 meets and exceeds below performance

API CH-4

Features/Benefits:

- **Superior protection:** High performance additive system provides very good wear protection to pistons, rings, cylinder liner, and valve train.
- **Superior soot control:** Special detergent additives prevent soot buildup in the engine, thereby preventing soot-induced thickening and ensuring efficient lubrication.
- **Improved engine cleanliness:** Superior oxidation resistance prevents sludge formation, oil thickening, and controls deposit ensuring a cleaner engine throughout the recommended oil drain period.

Application:

- Small commercial vehicles conforming to BS III and prior emission norms.
- Minivans, Pickup trucks, Diesel 3-Wheelers, etc.

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.864
Kinematic Viscosity @ 40°C, cSt	ASTM D445	103.50
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.30
Viscosity Index	ASTM D2270	141
Flash Point (COC), °C	ASTM D92	242
Pour Point, °C	ASTM D97	-30
Total Base Number, mg KOH/g	ASTM D2896	7.8

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:  
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:  
The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.