

PRIMA PRO 15W-40 CH-4

Tractor Engine Oil

Product Description

Veedol Prima Pro 15W-40 CH-4 diesel engine oil formulated with performance additives to deliver superior performance in tractor engines meeting TREM-IIIA emission norms.

The synthetic blend with balanced performance additives helps maintain viscosity for longer duration providing extended drain capability. It offers superior protection against wear, deposits, and maintains engine cleanliness.

Performance Specifications:

Veedol PRIMA PRO 15W-40 CH-4 meets & exceeds the performance requirements of

- API CH-4

Application:

- Recommended for Indian and international tractors meeting TREM-IIIA and prior emission norms.
- Suitable for combined harvesters, construction equipment and DG sets as well.
- Recommended oil drain interval 500 hours*

Features/Benefits:

- **Efficient soot control:** Special detergent and dispersant additives in the oil ensure reduced soot buildup, preventing deposits that can hinder engine efficiency and longevity.
- **Superior protection:** High performance additive system provides very good wear protection to pistons, rings, cylinder liner, and valve train.
- **Improved Engine Cleanliness:** Ability to resist sludge formation, oil thickening, and deposits ensures a cleaner engine throughout the entire recommended oil drain interval.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Density @ 29.5°C	cSt	D 4052	0.8530
Kinematic Viscosity @ 40°C	cSt	D 445	103.7
Kinematic Viscosity @ 100°C	cSt	D 445	14.69
Viscosity Index		D 2270	146
Flash Point	°C	D 92	242
Pour Point	°C	D 927	-30
Total Base Number	mgKOH/g	D 2896	7.8

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

**STORAGE**

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

**HEALTH, SAFETY AND ENVIRONMENT**

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.