



Heavy Pull Pro 15W-40 CF-4

Multigrade Engine Oil for Small Commercial Vehicles
Synthetic blend

PRODUCT DATA SHEET

Product Description:

Veedol Heavy Pull Pro 15W-40 CF-4 is a high-performance diesel engine oil designed to deliver superior performance for all types of small commercial vehicles. This synthetic blend is enriched with quality detergent and dispersant additives, which help maintain a clean engine for an extended period.

It provides superior protection against wear and deposits, ensuring very good engine cleanliness and longevity. The formulation is engineered to meet the demanding requirements of small commercial vehicles, offering reliable performance and protection under various operating conditions.

Performance Specification:

Veedol Heavy Pull Pro 15W-40 CF-4 meets and exceeds below performance

API CF-4

Features/Benefits:

- **Superior protection:** Synthetic blend fortified with high quality additives provide very good wear protection to engine components thereby reducing the maintenance cost.
- **Improved engine cleanliness:** Enhanced thermal and oxidation resistance prevents sludge formation, oil thickening, ensuring a cleaner engine throughout the recommended oil drain period.
- **Superior piston deposit control:** High detergency characteristic prevents soot buildup on the piston and inside ring grooves thereby helping to deliver consistent performance.

Application:

- Small commercial vehicles conforming to BS II and prior emission norms.
- Minivans, Pickup trucks, Diesel 3-Wheelers, etc.

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.864
Kinematic Viscosity @ 40°C, cSt	ASTM D445	110.46
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.69
Viscosity Index	ASTM D2270	137
Flash Point (COC), °C	ASTM D92	232
Pour Point, °C	ASTM D97	-30
Total Base Number, mg KOH/g	ASTM D2896	6.5

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.