

PRIMA ECO 20W-40 CF-4

Tractor Engine Oil

Product Description

Veedol Prima Eco 20W-40 CF-4 is a good quality engine oil formulated for lubricating non-turbo and turbocharged diesel engines in tractors and other agricultural machines. It is made from paraffinic base stocks and fortified with selected additives to deliver satisfactory performance in tractors.

Performance Specifications:

Veedol PRIMA ECO 20W-40 CF-4 meets & exceeds the performance requirements of

- API CF-4

Application:

- Suitable for all tractors manufactured by various OEMs.
- Recommended oil drain interval 300 hours*

Features/Benefits:

- **Efficient soot control:** Special detergent and dispersant additives in the oil ensure reduced soot buildup, preventing deposits that can hinder engine efficiency and longevity.
- **Assured protection:** High performance additive system provides very good wear protection to pistons, rings, cylinder liner, and valve train.
- **Better Engine Cleanliness:** Ability to resist sludge formation, oil thickening, and deposits ensures a cleaner engine throughout the entire recommended oil drain interval.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Density @ 29.5°C	cSt	D 4052	0.8810
Kinematic Viscosity @ 40°C	cSt	D 445	112.1
Kinematic Viscosity @ 100°C	cSt	D 445	14.35
Viscosity Index		D 2270	130
Flash Point	°C	D 92	230
Pour Point	°C	D 927	-24
Total Base Number	mgKOH/g	D 2896	10.2

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

**STORAGE**

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

**HEALTH, SAFETY AND ENVIRONMENT**

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.