



PRODUCT DATA SHEET

Product Description:

Veedol Prima Eco 20W-40 CF-4 is a good quality engine oil formulated for lubricating non-turbo and turbocharged diesel engines in tractors and other agricultural machines. It is made from paraffinic base stocks and fortified with selected additives to deliver satisfactory performance in tractors.

Performance Specification:

Veedol Prima Eco 20W-40 CF-4 meets and exceeds below performance

API CF-4

Features/Benefits:

- **Assured protection:** High performance additive system provides very good wear protection to pistons, rings, and cylinder liner under severe conditions.
- **Efficient soot control:** Special detergent and dispersant additives in the oil ensure reduced soot buildup, preventing deposits that can hinder engine efficiency and longevity.
- **Very good engine cleanliness:** Ability to resist sludge formation, oil thickening, and deposits ensures a cleaner engine throughout the entire recommended oil drain interval.

Application:

- Suitable for all tractors manufactured by various OEMs.
- Recommended oil drain interval 300 hours*

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.881
Kinematic Viscosity @ 40°C, cSt	ASTM D445	112.10
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.35
Viscosity Index	ASTM D2270	130
Flash Point (COC), °C	ASTM D92	230
Pour Point, °C	ASTM D97	-24
Total Base Number, mg KOH/g	ASTM D2896	10.2

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

* Oil drain period recommended above is under standard test conditions. It may vary based on actual driving and vehicle condition. Please refer to the vehicle service manual for oil specification and drain interval for specific vehicle types.