



Take-Off 4S Pro Scooter 10W-30 SN / MB
Four Stroke Gearless Scooter Engine Oil
Synthetic Blend

PRODUCT DATA SHEET

Product Description:

Veedol Take-Off 4S Pro Scooter 10W-30 SN / MB is a high-quality synthetic blend engine oil specifically designed for gearless scooters. It provides superior protection, thermal stability, and high oxidation resistance, keeping the engine running smoothly under all conditions. The synthetic blend fortified with special additives helps maintain a cleaner engine and improves efficiency in modern scooter engines.

Veedol Take-Off 4S Pro Scooter 10W-30 SN / MB delivers instant cold start and enhances fuel efficiency ensuring optimal performance.

Performance Specification:

Veedol Take-Off 4S Pro Scooter 10W-30 SN / MB meets and exceeds below performances

API SN
JASO MB T903: 2016

Features/Benefits:

- **Enhanced Performance:** Delivers superior protection against wear and tear, ensuring engine longevity.
- **Superior Cold Start Protection:** Provides quick lubrication in low temperatures for reduced engine wear during startup.
- **Improved High-Temperature Stability:** Synthetic blend helps maintain viscosity and performance under high-temperature conditions, preventing breakdown of oil.
- **Superior Cleaning Action:** Helps in keeping the engine clean by preventing sludge and deposit formation.

Application:

- Recommended for modern scooters fitted with automatic transmissions and dry clutch.
- Suitable for air and water-cooled four stroke engines with automatic transmission.

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.853
Kinematic Viscosity @ 40°C, cSt	ASTM D445	70.1
Kinematic Viscosity @ 100°C, cSt	ASTM D445	10.70
Viscosity Index	ASTM D2270	141
Flash Point (COC), °C	ASTM D92	240
Pour Point, °C	ASTM D97	-33
Total Base Number, mg KOH/g	ASTM D2896	7.2

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:
The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.