Alwro

Wire Rope Oil

Product Description:

Veedol Alwro is formulated with hydro processed premium base oils and performance additives. The special light bodied product helps in deep penetration and uniform distribution, thereby providing a film coating over the rope wires.

Features/Benefits:

- Provides excellent protection against rusting and corrosion
- Good penetrating property.
- Forms a good protective oil film on the applied surface.

Application:

- Recommended for wire ropes used in elevators

Typical Properties:

Parameters	Test Method	Alwro
Appearance	Visual	Clear & Bright
Kinematic Viscosity @ 40°C, cSt	ASTM D445	11.0 - 16.0
Viscosity Index	ASTM D2270	100
Flash Point (COC), °C	ASTMD92	180

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH, SAFETY AND ENVIRONMENT
The informtion on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

VEEDOL CORPORATION LIMITED
Corporate Office: 902, Godrej TWO, Vikhroli, Eastern Express Highway, Mumbai-400 079.
Regd. Office: Yule house, 8, Dr. Rajendra Prasad Sarani, Kolkata-700 001, West Bengal, India.
www.veedolindia.com