

# Avalon HVI 100 Pro

Extra Heavy Duty Long Drain Hydraulic Oil

## Product Description:

Veedol Avalon HVI 100 Pro is a high viscosity index, shear stable hydraulic oil meant for systems working under wide temperature range.

Blended with premium quality base oils, advanced zinc-based additives, and shear stable viscosity modifiers, it exhibits excellent viscosity control under severe mechanical stress and a wide range of temperatures. It also provides outstanding protection to the hydraulic systems in most demanding conditions.

## Performance Specifications:

Veedol Avalon HVI 100 Pro meets & exceeds the performance requirements of

- IS 11656:1986 (Reaffirmed 2013)
- Denison Hydraulics HF-0, HF-1, HF-2
- AIST 127

## Features/Benefits:

- Outstanding resistance to degradation at high pressure, temperature and mechanical stress provide longer oil life.
- Excellent thermal and oxidation stability minimizes deposit formation, enhances system cleanliness, helps extend oil and filter life, thus reducing maintenance cost.
- High viscosity index resists change in viscosity over wide range of temperatures improving hydraulic efficiency.
- Excellent hydrolytic stability provides improved protection to yellow metals in hydraulic system.

## Application:

- Moderate- to high-pressure hydraulic systems operating outdoors in severe cold regions or where there is a wide variation in ambient temperature.
- Hydraulic equipment requiring high viscosity index hydraulic fluids.
- Hydraulic equipment used in marine, construction, mining, and oil-industries.

## Typical Properties:

Test Parameters	Test Method	Result
Density at 29.5°C	ASTM D4052	0.858
Kinematic Viscosity @ 40°C, cSt	ASTM D445	100.0
Kinematic Viscosity @ 100°C, cSt	ASTM D445	12.9
Viscosity Index	ASTM D2270	125
Flash Point (COC), °C	ASTMD92	245
Pour Point, °C	ASTM D97	-30
Copper Corrosion at 100°C, 3 hours	ASTM D130	1a
Foaming Tendency/ Stability		
Sequence I, mL/mL	ASTM D892	0/0
Sequence II, mL/mL		10/0
Sequence III, mL/mL		0/0
Rust Test	ASTM D665	Pass

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



### STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



### HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.