

EX3 ENGINE OIL

High Performance Engine Oil

Product Description

Veedol EX3 Engine Oil is a specially designed automotive engine oil for backhoe loaders. It is formulated with premium quality base oil and selected performance additives delivering excellent load carrying property.

Veedol EX3 Engine Oil possesses high thermal and oxidation stability and delivers prolong protection to high performance engines of heavy-duty construction equipment.

Performance Specifications:

Veedol EX3 Engine Oil meets & exceeds the performance requirements of

API CI-4

Application:

- Suitable for heavy construction equipment.

Features/Benefits:

- Ensures engine durability under severe operating conditions.
- Excellent oxidation and thermal stability.
- Reduces piston deposits and oil consumption.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Kinematic Viscosity @ 100°C	cSt	D 445	14.8
Viscosity Index		D 2270	140
Flash Point	°C	D 92	240
Pour Point	°C	D 927	-30

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.