

EX3 REAR AXLE OIL

High Performance Axle Oil

Product Description

Veedol EX3 Rear Axle Oil is a specially designed gear oil for backhoe loaders. It is formulated with premium quality base oil and selected performance additives delivering excellent load carrying property.

Performance Specifications:

Veedol EX3 Rear Axle Oil meets & exceeds the performance requirements of

- API GL-4
- IS 1118- 2019

Application:

- Suitable for heavy construction equipment.

Features/Benefits:

- High load carrying capacity for continuous high speed and high torque service.
- Excellent oxidation and thermal stability.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Kinematic Viscosity @ 100°C	cSt	D 445	16.50
Viscosity Index		D 2270	96
Flash Point	°C	D 92	240
Pour Point	°C	D 927	-6

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.