

EX3 TRANSMISSION OIL

High Performance Transmission Oil

Product Description

Veedol EX3 Transmission Oil is a specially designed automotive gear oil for backhoe loaders. It is formulated with premium quality base oil and selected performance additives delivering trouble free operations of gears, bearings parts of equipment.

Veedol EX3 Transmission Oil possesses low coefficient of friction thus permitting clutch plate to engage smoothly as the transmission shift.

Performance Specifications:

Veedol EX3 Transmission Oil meets & exceeds the performance requirements of

General Motors Type 'A' Suffix 'A'

Application:

- Suitable for heavy construction equipment.

Features/Benefits:

- Excellent oxidation and thermal stability.
- Low temperature fluidity and foam control.
- Excellent anti-wear and anti-corrosion protection.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Kinematic Viscosity @ 100°C	cSt	D 445	7.500
Viscosity Index		D 2270	150
Flash Point	°C	D 92	224
Pour Point	°C	D 927	-42

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.