

Lubricants

HDC TURBO SPRINT 15W-40 API CF-4

DIESEL ENGINE OIL FOR LCV'S & HCV'S

DESCRIPTION

Veedol HDC Turbo Sprint 15W-40 is formulated with combination of high quality base oils and specially selected additives for heavy duty diesel engines of LCVs and HCVs.

Veedol HDC Turbo Sprint 15W-40 is a high performance diesel engine oil that provides protection to the engine components, optimizes engine performance and reduces oil consumption.

PERFORMANCE SPECIFICATIONS

Meets & Exceeds the performance requirements of

- API CF-4
- MB 228.3
- IS 13656:2014 EDL 5
- · ACEA E3-level, A2/B2
- MAN 3275
- Volvo VDS
- MTU Type 2
- Mack EOK

FEATURES/BENEFITS

- · Higher Turbocharger protection and longer turbo life,
- · Better piston cleanliness and clean engine.
- · Enhanced anti-wear performance for longer engine life.
- · Improved soot handling.
- · Maintains fuel economy.

APPLICATIONS

Recommended for latest generation turbocharged diesel engines used in trucks, tractors, LCVs, and cars,

CHARACTERISTICS

Test Parameter	Test Method	Typical Value
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	14.5
Viscosity Index	ASTM D 2270	140
Flash Point, (COC) °C	ASTM D 92	242
Pour Point, °C	ASTM D 97	-30
CCS Viscosity @ -20°C, mPa.s	ASTM D 5293	5600