

Lubricants

HEAVY PULL 15W-40 API CF-4

MULTIGRADE DIESEL ENGINE OIL

DESCRIPTION

Veedol Heavy Pull 15W-40 is a high performance multigrade engine oil providing superior protection to diesel engines operating under heavy load applications. It is intended for diesel engines where-in API CF-4 oil is desired.

PERFORMANCE SPECIFICATIONS

Meets & Exceeds the performance requirements of

- API CF-4
- IS 13656:2014 EDL 4

APPLICATIONS

Specially developed multigrade engine oil recommended for use in Tata Ace, Piaggio Ape, Mahindra Champion, Force Minidor, Atul Shakti, Bajaj Auto Rickshaws, Vikram and other high performance new generation diesel engines.

FEATURES/BENEFITS

- Possesses extra film strength that minimizes engine wear even under heavy load, high operating temperatures, stop & go conditions.
- High thermal and oxidation stability helps to achieve longer drain interval and also keeps top-up requirements to a minimum.
- Keeps engine clean, reduces piston deposits, oil consumption and optimizes engine performance.

CHARACTERISTICS

Test Parameter	Test Method	Typical Value
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	14.7
Viscosity Index	ASTM D 2270	138
Flash Point, (COC) °C	ASTM D 92	242
Pour Point, °C	ASTM D 97	-30
CCS Viscosity @ -20°C, mPa.s	ASTM D 5293	6000