

HEAVY PULL CNG 20W-50 CF/SF

Multigrade CNG Engine Oil

Product Description

Veedol Heavy Pull CNG 20W-50 CF/SF is a dedicated engine oil designed for lubrication of small commercial vehicles using compressed natural gas. Fortified with special additives, it provides assured protection against wear, oxidation, nitration, and deposits.

Veedol Heavy Pull CNG 20W-50 provides good performance in the challenging operating environments encountered by Compressed Natural Gas (CNG).

Performance Specifications:

Veedol Heavy Pull CNG 20W-50 CF/SF meets & exceeds the performance requirements of

API CF/SF

Application:

- Light commercial vehicles conforming to BS II and prior emission norms.
- Suitable for small commercial vehicles running on compressed natural gas (CNG) and conventional fuels.
- Compatible with Exhaust Gas Recirculation (EGR) Systems, Three-Way Catalysts, and other emission reduction systems.

Features/Benefits:

- **Assured protection:** Active anti-wear technology provides protection to pistons, rings, cylinder liner lowering servicing cost.
- **Clean engine:** Resistance to oxidation helps prevent sludge generation, thereby maintaining clean engines and extending oil life.
- **Dual fuel performance:** Provides very good performance in medium and light-duty vehicles fueled with CNG as well as conventional fuels.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Density @ 29.5°C	cSt	D 4052	0.8790
Kinematic Viscosity @ 40°C	cSt	D 445	160.1
Kinematic Viscosity @ 100°C	cSt	D 445	18.75
Viscosity Index		D 2270	132
Flash Point	°C	D 92	252
Pour Point	°C	D 927	-27
Total Base Number	mgKOH/gm	D 2896	5.4

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.


STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.


HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.