

MAX-PRO 15W-40 CI-4 PLUS

Premium Heavy-duty Diesel Engine Oil

Product Description

Veedol Max-Pro 15W-40 CI-4 Plus is a heavy-duty diesel engine oil formulated with high-performance additives to deliver excellent performance in modern engines.

The advanced synthetic blend offers long life and extended drain capability, providing excellent viscosity and soot control. It offers outstanding protection against wear for heavy-duty diesel engines operating under a wide variety of service conditions. Suitable for engines fitted with exhaust gas recirculation (EGR).

Performance Specifications:

Veedol Max-Pro 15W-40 CI-4 Plus meets & exceeds the performance requirements of

- API CI-4 Plus
- ACEA E9-2016
- Volvo VDS-4
- Cummins CES 20081
- MB 228.31
- CAT ECF-3

Application:

- On-highway and off-highway heavy-duty diesel vehicles meeting BS IV / Euro IV norms.
- Naturally aspirated and turbocharged diesel engines. Mixed fleet of BS IV and older generation vehicles.
- Recommended oil drain interval 90,000Km*.

Features/Benefits:

- **Unmatched protection:** Exceptional additive system provides outstanding wear protection characteristics.
- **Excellent engine cleanliness:** High resistance to sludge formation, oil thickening, and deposit control ensure a cleaner engine throughout the recommended oil drain period.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

- **Trouble free operation during long drain service intervals:** Advanced synthetic blend resists thermal and oxidation degradation ensuring trouble free operation during longer oil drain period.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Density @ 29.5°C	cSt	D 4052	0.8620
Kinematic Viscosity @ 40°C	cSt	D 445	102.3
Kinematic Viscosity @ 100°C	cSt	D 445	14.50
Viscosity Index		D 2270	146
Flash Point	°C	D 92	248
Pour Point	°C	D 927	-30
Total Base Number	mgKOH/g	D 2896	7.2

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

VEEDOL CORPORATION LIMITED

[formerly Tide Water Oil Co. (India) Limited]

Corporate Office: 902, Godrej TWO, Vikhroli, Eastern Express Highway, Mumbai-400 079.

Regd. Office: Yule house, 8, Dr. Rajendra Prasad Sarani, Kolkata-700 001, West Bengal, India.

www.veedolindia.com