Alithex S3 Grease

Multipurpose Lithium Grease

Product Description:

Veedol Alithex S3 Grease series is superior quality multipurpose Lithium based grease suitable for lubricating various equipment. Formulated with highly refined base oil, rust and oxidation inhibitors, these greases are suitable for a wide range of applications.

Features/Benefits:

- Very good water wash-out resistance helps stay-in-place performance of grease in wet operating conditions.
- Excellent rust and anti-wear properties ensure component protection.
- High oxidation stability helps reduce base oil degradation, promoting long service life.

Application:

- Lubrication of ball and roller bearing in various industries.
- Lightly loaded industrial machineries.
- General lubrication in non-demanding applications.
- Operating temperature range -10°C to +120°C

Additional Information:

Properties	Test method	Alithex S3 Grease
NLGI Grade		NLGI 3
Soap / Thickener type		Lithium
Color	Visual	Yellowish
Worked Penetration @ 25°C, 60 double strokes	ASTM D217	245
Drop point, °C	ASTM D2265	185
Copper Corrosion, 100°C for 24hrs	ASTM D4048	1b
Base oil viscosity at 40°C, cSt	ASTM D 445	105

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH, SAFETY AND ENVIRONMENT
The informtion on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

VEEDOL CORPORATION LIMITED
Corporate Office: 902, Godrej TWO, Vikhroli, Eastern Express Highway, Mumbai-400 079.
Regd. Office: Yule house, 8, Dr. Rajendra Prasad Sarani, Kolkata-700 001, West Bengal, India.
www.veedolindia.com