



Avalon Eco 68

R&O type Hydraulic Fluid and Circulating Oil
Previous name: Atline 68

PRODUCT DATA SHEET

Product Description:

Veedol Avalon Eco 68 is a high-quality rust and oxidation type hydraulic and circulating oil. It possesses very good anti-wear, anti-foaming and oxidation resistance properties that help machines to operate efficiently.

Features/Benefits:

- **Very good oxidation resistance** ensures less deposits and cleaner system,
- **Superior protection against rust and corrosion** helps reduce maintenance costs.
- **Good water separability and** increases system efficiency.

Application:

- Suitable for hydraulic machinery requiring R&O type of oils.
- Lubrication of line shafts, industrial equipment bearing.

Typical Properties:

Parameters	Test Method	68
Density at 29.5°C	ASTM D4052	0.870
Kinematic Viscosity @ 40°C, cSt	ASTM D445	68.5
Kinematic Viscosity @ 100°C, cSt	ASTM D445	8.74
Viscosity Index	ASTM D2270	99
Flash Point (COC), °C	ASTM D92	242
Pour Point, °C	ASTM D97	-9

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.