



Calci EP Grease

Calcium Grease
Previous name: Anepro

PRODUCT DATA SHEET

Product Description:

Veedol Calci EP Grease is superior quality multipurpose calcium soap thickened grease that offers excellent protection from rust and corrosion. It is particularly suited to cope with wet and corrosive environment. Formulated with anti-wear and oxidation resistant additives, it ensures long service life.

Features/Benefits:

- **Excellent water wash-out resistance** helps stay-in-place performance of grease in wet operating conditions.
- **Very good anti-rust and anti-wear properties** ensure component protection.
- **Superior mechanical stability** helps maintain grease structure under loading conditions.

Application:

- Wheel bearings and pumps operating at moderate temperature.
- General lubrication in non-demanding applications.
- Bearings of roll mills experiencing high water contamination.
- Anepro 11 can be recommended for lubrication of sugar mill journal bearings.
- Suitable for centralized lubrication system.
- Operating temperature range -10°C to +65°C



Calci EP Grease

Calcium Grease
Previous name: Anepro

PRODUCT DATA SHEET

Typical Properties:

Properties	Test method	Calci EP 2 Grease	Calci EP 1 Grease
NLGI Grade		NLGI 2	NLGI 1
Soap / Thickener type		Calcium	Calcium
Color	Visual	Yellowish brown	Yellowish brown
Texture	Visual	Smooth, tacky	Smooth, tacky
Worked Penetration @ 25°C, 60 double strokes	ASTM D217	285	318
Drop point, °C	ASTM D2265	105	103
Copper Corrosion @ 75°C, 24hr	ASTM D4048	Negative	Negative
Four Ball Weld Load, kg	ASTM D2596	250	250
Base oil viscosity @ 40°C, cSt	ASTM D445	105	105

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.