



GUNK Veedol Motor Flush

TECHNICAL DATA SHEET

Product Description:

Gunk Veedol Motor Flush is engineered to improve the oil drain for vehicles over 20,000 kms. The super concentrated cleaning agents actively clean deposits in the engine and help reduce sludge and varnish on cylinder heads. The product is made with high-quality solvents for effective cleaning. It dissolves sludge, lacquer, etc and is compatible with all motor oils.

Benefits

- The engine gets cleaned like new
- Ability to clean out minuscule particles in the engine that the oil filter cannot filter out
- Cleans Built-up deposits, gums and varnish formation
- Flushing cleans the engine parts of sludge
- Travel longer between oil changes
- Improves engine performance

Application:

Recommended for all 2-wheelers, 4-wheelers, heavy duty vehicles

Direction for use:

- Allow the car's engine to run until it reaches normal operating temperature
- Turn engine off, then pour entire bottle into oil crankcase
- The engine should run for 5 to 15 minutes at idle to circulate flush
- Drain crankcase and remove the oil filter
- Replace drain plug and install the new oil filter
- Refill crankcase with new motor oil.

Typical Properties

Test Parameter	Test Method	Specification
Appearance	Visual	Clear Liquid
Colour	Visual	Pale Yellow - Yellow
Density @29.5 °C	ASTM D 4072	0.80 ± 0.05
Distillation range, °C	ASTM D 86	120 - 170
Flash Point (PMCC)	ASTM D 93	>26
Acid Value, mg KOH / gm	ASTM D 974	1.0 max

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacturing processes and at different blending locations. The information contained herein is subject to change without notice.



Packing: 40ml, 50 ml, 250ml, 5 litre

Storage: Keep in cool dry place

Best Before 24 months from the date of Manufacture

Caution: Highly Flammable harmful or fatal if swallowed, Eye & Skin irritant.

Exposure Symptoms:

Inhalation: Exposure to vapor may cause light headedness or drowsiness. Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact: The use of gloves is recommended, but not necessary.

Eye Contact: Liquid may cause slight irritation. If eye irritation persists, rinse with water for several minutes. Wear safety glasses

Ingestion: Do not induce vomiting. If swallowed, rinse your mouth and drink plenty of water. If symptoms develop from exposure, seek medical attention