



## GUNK Veedol Radiator Flush

### TECHNICAL DATA SHEET

#### Product Description:

Gunk Veedol Radiator Flush is a concentrated formula which removes harmful deposits on the radiator tubes that result from oxidations of coolant and corrosion of metal. Dissolves contaminants containing and oil in radiators, heating systems, pipes and in engines. Improves efficiency of heat transfer from engine to radiator, eliminates pre-ignition problems, engine oil degradation, and thermal distortion of engine components.

#### Benefits:

- Effectively removes sludge, rust and scales
- Improves heat transfer from engine to cooling fluid
- Extends Water Pump Lifespan
- Prevents Rust and Foam
- Removes Contaminants
- Inspects for Cooling Issues
- Prevents Acidic Anti-Freeze
- Compatible with Anti-Freeze

#### Application:

Add appx. 5 percent by volume in the radiator and keep the engine idling for at least 10 minutes or drive for 15 minutes and then flush with fresh water till water runs clear.

Recommended for all types of 4-wheelers, heavy duty vehicles

#### Typical Properties:

Test Parameter	Test Method	Specification
Appearance	Visual	Clear
Colour	Visual	Straw Liquid
Odour	-----	Mild
Density @ 29.5 °C, gm/ml	ASTM D 4052	0.9 – 1.1
pH	pH Meter	8.4 – 8.6

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacturing processes and at different blending locations. The information contained herein is subject to change without notice

Packing: 50 ml, 200 ml, 250 ml, 5 Ltr

Storage: Keep in cool dry place. Shelf life: 24 months

**Caution:** Avoid contact with eyes. Wear safety gloves for application. Keep away from fire or flame. Harmful or fatal if swallowed, do not induce vomiting, call physician immediately. Contains aromatic solvents. Vapour harmful. Avoid contact with skin.

