



Heavy Pull Premium 10W-30 CK-4

Premium Small Commercial Vehicle Engine Oil
Advanced synthetic blend

PRODUCT DATA SHEET

Product Description:

Veedol Heavy Pull Premium 10W-30 CK-4 is an advanced synthetic blend oil specifically formulated for small commercial vehicles. Designed to meet the stringent demands of modern small commercial vehicles powered by diesel, petrol and CNG those operate in stop-and-go traffic, this advanced formulation provides unmatched protection against wear, oxidation, and oil breakdown, ensuring engine cleanliness and extended service intervals.

Veedol Heavy Pull Premium 10W-30 CK-4 provides unmatched protection for engines of small commercial vehicles and pick-up trucks meeting BS VI emission norms, and equipped with Exhaust Gas Recirculation (EGR), Diesel Particulate Filters (DPF), and Selective Catalytic Reduction (SCR) emission control technologies.

Performance Specification:

Veedol Heavy Pull Premium 10W-30 CK-4 meets and exceeds below performances

API CK-4

Features/Benefits:

- **Unmatched protection under stop-and-go conditions:** Advanced additive technology minimizes wear, extending engine life in demanding driving conditions.
- **Excellent oxidation and thermal stability:** Advanced synthetic blend resists oxidation and thermal breakdown, enhancing engine durability and prolonging oil life for reliable performance in demanding conditions.
- **Excellent engine cleanliness:** Resistance to sludge formation, deposit control and oil thickening ensures a cleaner engine throughout the recommended oil drain period.

Application:

- Small commercial diesel vehicles meeting BS VI / Euro VI norms and with the manufacturer's recommendation to use API CK-4 category SAE 10W-30 grade oils.
- Suitable for diesel, petrol and CNG powered small commercial vehicles.
- Pick-up trucks, Vans, Utility vehicles, Minibuses, etc.

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.843
Kinematic Viscosity @ 40°C, cSt	ASTM D445	69.60
Kinematic Viscosity @ 100°C, cSt	ASTM D445	10.91
Viscosity Index	ASTM D2270	147
Flash Point (COC), °C	ASTM D92	234
Pour Point, °C	ASTM D97	-36
Total Base Number, mg KOH/g	ASTM D2896	7.6

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.