



Multigear Plus 85W-140 HD

Heavy Duty Gear and Transmission oil

TECHNICAL DATA SHEET

Description:

Veedol Multigear Plus 85W-140 HD oil is extreme pressure gear lubricant of heavy duty type. It conforms to API Service Classification GL-5 and other performance requirements. Veedol Multigear Plus 85W-140 HD is formulated with high performance additive system for complete protection under heavy load application.

Performance Specifications:

Meets & exceeds the performance requirements of

- API GL-5
- US MIL-L-2105D
- IS:1118-1992

Features/Benefits:

- Possesses high load carrying capacity for continuous high speed and high torque service.
- Excellent Protection to gear components against wear under heavy loads.

Application:

Veedol Multigear Plus 85W-140 HD is recommended for hypoid gear differentials, mechanical transmissions and drive axles operating under severe duty conditions for use in Tata Motors and other vehicle manufacturer.

Typical Properties:

Test Parameters	Test Method	Typical Values
Kinematic Viscosity, @ 100°C, cSt	ASTM D 445	26.3
Viscosity Index	ASTM D 2270	98
Flash Point (COC), °C	ASTM D 92	248
Pour Point, °C	ASTM D 97	-15

Properties mentioned above are typical only and minor variations which do not affect the product performances, are to be expected in normal manufacturing.