



Rapid Kool GL Green

Premium Quality Radiator Coolant

PRODUCT DATA SHEET

Product Description:

Veedol Rapid Kool GL Green is a premium quality glycol-based radiator coolant suitable for automotive and stationary engines. Veedol Rapid Kool GL Green provides superior protection even under heavy duty applications and safeguards engine and cooling system against pitting, overheating, corrosion and cavitation erosion. It is free from borates, nitrates, silicates, phosphates and amines.

Features/Benefits:

- Rapid heat removal facilitates excellent heat transfer, ensuring optimum engine cooling and longer engine life.
- Anti-rust shield selectively acting and protecting radiator interior surfaces against rust and corrosion.
- Protection against corrosion of various metals like cast iron, copper, aluminum, brass found in radiators of modern vehicles.
- Enhanced water pump performance.
Does not harm non-metallic components, gaskets, hoses etc.

Application:

- Recommended for use in radiators of HCV's, LCV's & passenger cars manufactured by Tata Motors, Eicher, Force Motors, Hyundai, Honda etc.
- Suitable for use in radiators of all commercial vehicles, trucks, tractors, earth movers, jeeps, LCVs and passenger cars.

Directions for use:

Recommended dilution ratio (Coolant: Drinking Water)

- 1 part of Veedol Rapid Kool GL Green Coolant: 3 parts of drinking water
- Change the radiator coolant every 6 months for optimum performance

Typical Properties:

Test Parameter	Typical Test Value
Appearance	Clear
Colour	Green
Reserve Alkalinity (ml of 0.1N HCL)	7.1
pH	9.0
Freezing Point (°C)	-8
Test on 1:3 dilution (1 part coolant: 3-part drinking water)	
Foaming Tendency	Passes Test
Copper Corrosion, 24 hrs at 88°C	No Corrosion
Cast Iron Corrosion, 24 hrs at 88°C	No Corrosion
Aluminum Corrosion, 24 hrs at 88°C	No Corrosion

* Product Contains 15% Glycol

Caution:

Do not open the radiator cap in hot condition.

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:
The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.