



Ruspro DW 02

Rust Preventive

TECHNICAL DATA SHEET

Product Description:

Veedol Ruspro DW 02 is water displacing type, soft film, solvent deposited, corrosion preventives.

Veedol Ruspro DW 02 can be applied directly to water wet metal surfaces, where it displace water, leaving a protective film. It can be applied either by dipping or by spraying. Veedol Ruspro DW 02 has excellent spreading and forms a protective film which can be removed by wiping off.

Features/ Benefits:

- Forms thin oily film of good mechanical strength which can withstand subsequent handling.
- Excellent resistance to salt spray.
- Very good water displacing properties.
- Excellent protection even in severe conditions.

Application:

- Veedol Ruspro DW 02 has wide application for protection of components with high degree of finish in machine shops and heavy machinery.
- Veedol Ruspro DW 02 recommended for protection of tools, fasteners which have high degree of finish and also can be applied on components.

Typical Properties:

| Characteristics | Typical value |
|------------------------|--------------------|
| Appearance | Clear Amber Liquid |
| Flash Point | 40 °C |
| Specific Gravity @30°C | 0.828 |
| Protection - Indoors | 6 months |
| Protection - Outdoors | 2 months |

Properties mentioned above are typical only and minor variations which do not affect the product performances, are to be expected in normal manufacturing.