



## **Product Description:**

Veedol Transgear Dex II is a high-quality automatic transmission fluid made from highly refined base stocks and carefully selected additives. It provides superior performance in terms of oxidation resistance, protection against wear and corrosion for the automatic transmission system and operates effectively across a wide range of temperatures.

## **Performance Specification:**

Veedol Transgear Dex II meets & exceeds below performance

|             |                  |                                 |
|-------------|------------------|---------------------------------|
| GM Dex II   | Caterpillar TO-2 | MB 236.7, 236.6, 236.5          |
| Allison C-4 | MAN 339 Z1 & V1  | ZF-02F, 04D, 11A, 11B, 14A, 17C |

## **Features/Benefits:**

- **Superior wear protection** safeguards transmission components against wear and pitting, reducing maintenance costs.
- **High resistance to oxidation and thermal degradation** reduces deposits and extends the life of transmission components by resisting the effects of oxidizing agents and thermal stress.
- **Excellent compatibility** with transmission seal materials reduces the risk of leakages.

## **Application:**

- Recommended for automatic transmissions and power steering systems of vehicles.
- Also suitable for automatic gearboxes, torque converters where the manufacturer has recommended the use of DEXRON II fluid.

## **Typical Properties:**

| Parameters                       | Test Method | Values |
|----------------------------------|-------------|--------|
| Density at 29.5°C                | ASTM D4052  | 0.852  |
| Kinematic Viscosity @ 40°C, cSt  | ASTM D445   | 36.40  |
| Kinematic Viscosity @ 100°C, cSt | ASTM D445   | 7.4    |
| Viscosity Index                  | ASTM D2270  | 175    |
| Flash Point (COC), °C            | ASTM D92    | 196    |
| Pour Point, °C                   | ASTM D97    | -45    |

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

### **STORAGE:**

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

### **HEALTH AND SAFETY**

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.