



Turbo Pro 15W-40 CI-4 Plus

Heavy-duty Diesel Engine Oil
Synthetic blend

PRODUCT DATA SHEET

Product Description:

Veedol Turbo Pro 15W-40 CI-4 Plus is a heavy-duty diesel engine oil formulated with high-performance additives to deliver superior performance in modern engines.

The synthetic blend ensures prolonged service life and extended drain intervals, offering very good control over viscosity and soot buildup. It offers superior protection against wear for heavy-duty diesel engines operating under a wide variety of service conditions. Suitable for engines fitted with Exhaust Gas Recirculation (EGR) systems.

Performance Specification:

Veedol Turbo Pro 15W-40 CI-4 Plus meets and exceeds below performance

API CI-4 Plus	Cummins CES 20077 / 76	Volvo VDS-3
ACEA E7-08	CAT ECF-1a	MB 228.3
	Mack EO-M	MAN 3275

Features/Benefits:

- **Superior protection:** High performance additive system provides superior wear protection to pistons, rings, cylinder liner, and valve train.
- **Improved engine cleanliness:** Superior resistance to sludge formation, oil thickening, and deposit control ensure a cleaner engine throughout the recommended oil drain period.
- **Superior viscosity control:** Special synthetic blend provides superior viscosity control, resisting thermal and oxidation degradation.

Application:

- On-highway and off-highway heavy-duty diesel vehicles meeting BS IV emission norms.
- Naturally aspirated and turbocharged diesel engines.
- Mixed fleet of BS IV and older generation vehicles.
- Recommended oil drain interval 75,000Km*

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.865
Kinematic Viscosity @ 40°C, cSt	ASTM D445	108.28
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.70
Viscosity Index	ASTM D2270	140
Flash Point (COC), °C	ASTM D92	250
Pour Point, °C	ASTM D97	-30
Total Base Number, mg KOH/g	ASTM D2896	8.8

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

* Oil drain period recommended above is under standard test conditions. It may vary based on actual driving and vehicle condition. Please refer to the vehicle service manual for oil specification and drain interval for specific vehicle types.