

Product Description:

Veedol Turbo Pro Fleet 15W-40 CI-4 Plus is a heavy-duty diesel engine oil formulated with high-performance additives to deliver excellent performance in modern engines.

The advanced formulation offers long life and extended drain capability, providing excellent viscosity and soot control. It offers outstanding protection against wear for heavy-duty diesel engines operating under a wide variety of service conditions. Suitable for engines fitted with exhaust gas recirculation (EGR).

Performance Specification:

Veedol Turbo Pro Fleet 15W-40 CI-4 Plus meets and exceeds below performances

API CI-4 Plus / SL, CI-4	Volvo VDS-3	CAT ECF-1a
ACEA E7-2008	MB 228.3	Mack EO-M
	Cummins CES 20077 / 76	Deutz DQC-II
	MTU Type 2	

Features/Benefits:

- **Unmatched protection:** Exceptional additive system provides outstanding wear protection characteristics.
- **Excellent engine cleanliness:** High resistance to sludge formation, oil thickening, and deposit control ensure a cleaner engine throughout the recommended oil drain period.
- **Trouble free operation during long drain service intervals:** Advanced synthetic blend resists thermal and oxidation degradation ensuring trouble free operation during longer oil drain period.

Application:

- On-highway and off-highway heavy-duty diesel vehicles of various OEMs meeting BS IV / Euro IV emission norms.
- Construction and mining equipment, diesel generators.
- Naturally aspirated and turbocharged engines.
- Mixed fleet of BS IV and older generation vehicles.

Typical Properties:

Parameters	Test Method	Results
Density @ 29.5°C	ASTM D4052	0.865
Kinematic Viscosity @ 40°C, cSt	ASTM D445	108.28
Kinematic Viscosity @ 100°C, cSt	ASTM D445	14.70
Viscosity Index	ASTM D2270	140
Flash Point (COC), °C	ASTM D92	250
Pour Point, °C	ASTM D97	-30
Total Base Number, mg KOH/g	ASTM D2896	8.8
CCS Viscosity@-20 °C, mPa.s	ASTM D5293	6360

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.