VC Grease

Calcium Based Grease

Product Description:

Veedol VC grease is a Calcium based, water resistant grease with a tackifier.

Performance Specifications:

Meets & exceeds the performance requirements of

- IS 506: 1993 (Reaffirmed 2006)

Features/Benefits:

- Good performance against water washouts
- Excellent performance in chassis applications due to better adhesion
- Good pumpability nature provides adequate dispensing of grease at all times.

Application:

Recommended for chassis lubrication of automobiles including commercial vehicles, tractors and other heavy duty equipments.

Typical Properties:

Test Parameters	Test method	Typical Values
Texture	--	Smooth
Soap type	--	Calcium
Worked Penetration, 60st @ 25°C	ASTM D217	300
Drop point, °C	ASTM D2265	96

Properties mentioned above are typical only and minor variations which do not affect the product performances, are to be expected in normal manufacturing.

STORAGE
All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH, SAFETY AND ENVIRONMENT
The informtion on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

VEEDOL CORPORATION LIMITED
Corporate Office: 902, Godrej TWO, Vikhroli, Eastern Express Highway, Mumbai-400 079.
Regd. Office: Yule house, 8, Dr. Rajendra Prasad Sarani, Kolkata-700 001, West Bengal, India.
www.veedolindia.com