



Wheel Bearing Grease

Sodium Based Grease

PRODUCT DATA SHEET

Product Description:

Veedol Wheel Bearing Special Grease is specially formulated soda based having high melting point.

Performance Specifications:

Meets & exceeds the performance requirements of

- IS 10647:83 (Reaffirmed 2019)

Features/Benefits:

- Fibrous structure helps in better retention of the grease under heavy shear operation.
- High dropping point wheel bearing grease for longer service life.
- Good tackiness properties providing excellent protection to wheel bearings.
- Excellent anti-rust properties.

Application:

- Veedol Wheel bearing special grease is recommended for wide application in tractors, automotive vehicles and industrial equipment.
- Not recommended for chassis lubrication / water pump bearing application.

Typical Properties:

Test Parameters	Test Method	Typical Values
Texture	--	Fibrous
Soap type	--	Sodium
Worked Penetration, 60st @25°C	ASTM D 217	265
Drop Point, °C	ASTM D 2265	190

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

STORAGE:

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

HEALTH AND SAFETY:

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested