



GUNK Veedol Petrol Additive

TECHNICAL DATA SHEET

Product Description:

Gunk Veedol Petrol Additive contains additives that help dissolve and remove harmful carbon, gum, and varnish deposits on fuel injectors. Without cleaning, deposits can lead to hard starts, lost acceleration and rough idling.

Gunk Veedol Petrol Additive eliminates start problems and rough engine running. It removes deposits on intake valves.

Application: Spark plugs and in combustion chamber

Benefits

- Excellent protection against rust and corrosion
- Protects and clean fuel system
- Octane number enhancement
- Allow higher compression ratio in the engine cylinder
- Improves fuel economy
- Cleans and dissolves harmful deposit

Typical Properties:

Test Parameter	Test Method	Specification
Appearance	Visual	Clear Liquid
Colour	Visual	Colorless
Density @29.5 °C	ASTM D 4072	0.80 ± 0.05
Flash Point, °C (PMCC)	ASTM D 93	60 minimum

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacturing processes and at different blending locations. The information contained herein is subject to change without notice.

Packing: 250 ml

Storage: Keep in cool dry place

Best Before 24 months from the date of manufacturer





Caution: Flammable harmful or fatal if swallowed, Eye & Skin irritant.

Exposure Symptoms:

Inhalation: Exposure to vapor may cause light headedness or drowsiness. Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact: The use of gloves is recommended, but not necessary.

Eye Contact: Liquid may cause slight irritation. If eye irritation persists, rinse with water for several minutes. Wear safety glasses

Ingestion: Do not eat or drink when using. If swallowed, rinse your mouth and drink plenty of water. If symptoms develop from exposure, seek medical attention