

Veedol TURBOSTAR 20W-50

Premium Passenger Car Engine Oil

Product Description:

Veedol Turbostar 20W-50 is a premium quality multi-grade engine oil formulated with premium base oils fortified with latest technology performance additives providing protection under wide variety of operating conditions.

Veedol Turbostar 20W-50 is suitable for use in modern petrol engine passenger cars where API SM & SAE 20W-50 oil is desired.

Performance Specifications:

Veedol TURBOSTAR 20W-50 meets and exceeds below performances

- API SM

Application:

- Recommended for all new generation cars made by Maruti, Hyundai, Tata Motors, Daewoo, Ford, Fiat, Opel, Honda, General Motors, Skoda, Mitsubishi, Toyota, and Peugeot.
- Also suitable for use in CNG/LPG cars

Features/Benefits:

- Possesses improved oxidation stability and anti-rust properties.
- Excellent protection under wide variety of operating conditions.
- High performance engine oil enhances power to achieve peak vehicle speed.
- Provides adequate cushions for reducing engine vibrations and delivers smoothest ride.
- Unique anti-wear formula keeps engine components protected and power maintained like new engine.
- Fully compatible with catalytic converter.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Appearance	-	Visual	Clear & Bright
Kinematic Viscosity @ 100°C	cSt	D 445	18.3
Viscosity Index		D 2270	123
Pour Point	°C	D 97	-24
Flash Point	°C	D 92	244

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

**STORAGE**

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

**HEALTH, SAFETY AND ENVIRONMENT**

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.