

Veedol POWERTRON 5W-30

Fully Synthetic Premium Engine Oil

Product Description:

Veedol Powertron 5W-30 is a premium quality fully synthetic engine oil with advanced engine care technology specially developed for modern generation passenger cars.

Veedol Powertron 5W-30 is a perfect blend of superior quality base oils and latest technology additive system that ensures optimum power, performance, fuel efficiency, protection, durability and lower emissions.

Performance Specifications:

Veedol POWERTRON 5W-30 meets and exceeds below performances

- API SN / SM / CF
- ILSAC GF-5

Application:

- Recommended for both Petrol and Diesel Engines.
- Turbocharged GDI engines, supercharged gasoline, multi-valve fuel injected engines found in passenger cars, SUV's, light trucks and vans.
- Suitable for use in all modern generation cars such as Toyota, Honda, Suzuki, Hyundai, Kia, Mercedes Benz, BMW, Skoda, Chevrolet, Nissan, Fiat, TATA Motors, etc.

Features/Benefits:

- Excellent piston deposit control property.
- Provides optimum performance and engine protection in harsh conditions.
- Superior protection against sludge formation and combustion contamination.
- Excellent cold temperature property providing cold start requirement.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Appearance	-	Visual	Clear & Bright
Kinematic Viscosity @ 100°C	cSt	D 445	11.2
Viscosity Index		D 2270	161
Total Base Number	mgKOH/g	D 2896	7.0
Pour Point	°C	D 97	-39
Flash Point	°C	D 92	238

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.