

## SPRINT 15W-40 CI-4 PLUS

Heavy-duty Diesel Engine Oil

### Product Description

Veedol Sprint 15W-40 CI-4 Plus is a heavy-duty diesel engine oil formulated with high-performance additives, ensuring protection and performance in engines meeting BS IV and older emission norms.

The advanced mineral blend provides assured protection against wear, deposits, and soot-related viscosity increase, ensuring optimal engine cleanliness and durability. Designed for use in both on-highway and off-highway applications, it excels in harsh operating environments, delivering good thermal and oxidation stability to provide reliable performance and extend the life of your engines.

### Performance Specifications:

Veedol Sprint 15W-40 CI-4 Plus meets & exceeds the performance requirements of

- API CI-4 Plus
- ACEA E7-08
- Volvo VDS-3
- Cummins CES 20077/76
- MB 228.3

### Application:

- Heavy-duty diesel vehicles meeting BS IV emission norms.
- Turbocharged and naturally aspirated diesel engines. Mixed fleet of BS IV and older generation vehicles.
- Recommended oil drain interval 60,000Km\*.

### Features/Benefits:

- **Assured protection:** High performance additive system provides very good wear protection to pistons, rings, cylinder liner, and valve train.
- **Enhanced viscosity control:** Advanced mineral blend provides very good viscosity control, resisting thermal and oxidation degradation throughout the recommended oil drain period.



#### STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



#### HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

- **Optimal engine cleanliness:** Resistance to sludge formation, oil thickening, and deposit control.

### Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Density @ 29.5°C	cSt	D 4052	0.8650
Kinematic Viscosity @ 40°C	cSt	D 445	108.2
Kinematic Viscosity @ 100°C	cSt	D 445	14.70
Viscosity Index		D 2270	140
Flash Point	°C	D 92	250
Pour Point	°C	D 927	-30
Total Base Number	mgKOH/g	D 2896	8.8

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



#### **STORAGE**

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



#### **HEALTH, SAFETY AND ENVIRONMENT**

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

#### **VEEDOL CORPORATION LIMITED**

[formerly Tide Water Oil Co. (India) Limited]

Corporate Office: 902, Godrej TWO, Vikhroli, Eastern Express Highway, Mumbai-400 079.

Regd. Office: Yule house, 8, Dr. Rajendra Prasad Sarani, Kolkata-700 001, West Bengal, India.

[www.veedolindia.com](http://www.veedolindia.com)