

SPRINT 20W-40 CF-4

Heavy-duty Diesel Engine Oil

Product Description

Veedol Sprint 20W-40 CF-4 engine oil is formulated with advanced mineral technology to meet the rigorous demands of heavy-duty diesel engines.

Veedol Sprint 20W-40 CF-4 provides reliable lubrication, assured wear protection, good deposit control, and enhanced oxidation stability, ensuring the engine operates efficiently. Its advanced mineral formula helps maintain optimal viscosity, extending engine life and reducing maintenance costs.

Performance Specifications:

Veedol Sprint 20W-40 CF-4 meets & exceeds the performance requirements of

- API CF-4

Application:

- Heavy-duty diesel vehicles conforming to BS II and prior emission norms.
- Turbo-charged or naturally aspirated diesel engines.
- Recommended oil drain interval 18,000Km*.

Features/Benefits:

- **Assured protection:** Active anti-wear technology provides protection to pistons, rings, cylinder liner lowering servicing cost.
- **Minimize piston deposit:** Special detergent additives prevent soot buildup on piston, minimize ring sticking and engine wear.
- **Enhanced corrosion protection:** Superior corrosion protection formula enhances engine performance and reliability.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Density @ 29.5°C	cSt	D 4052	0.8810
Kinematic Viscosity @ 40°C	cSt	D 445	112.1
Kinematic Viscosity @ 100°C	cSt	D 445	14.35
Viscosity Index		D 2270	130
Flash Point	°C	D 92	230
Pour Point	°C	D 927	-24

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.