



# SYNTHGLIDE 88

5W-30 | API SQ | ILSAC GF-7A

INTRODUCING  
NEXT-GEN  
FULLY SYNTHETIC



Elegant Power. Effortless Drive

## Product Description

**Veedol SYNTHGLIDE 88 5W-30** is a Next-Gen fully synthetic passenger car oil powered by EstoBioLide™, a unique bio-inspired technology delivering unmatched lubricity, superior cleanliness and longer oil life.

Formulated with advanced polymer chemistry, it ensures consistent power delivery, superior wear protection and smooth driving comfort.

## Features/Benefits



**Built to Resist Oxidation:** Advanced EstoBioLide™ chemistry resists viscosity breakdown and keeps the engine clean and responsive. The result is a smooth ride with effortless acceleration.



**Minimize Low-Speed Pre-Ignition:** Proven to reduce Low-Speed Pre-Ignition (LSPI) by up to 40%, this advanced formulation delivers superior protection for modern TGD and GDI engines.



**Unmatched Protection:** Engineered with advanced anti-wear chemistry, this oil delivers up to 77% better defense against wear and tear.



**Fuel Efficiency:** High shear stability ensures optimum lubrication, delivering improved mileage in city and highway riding.

## Performance Specifications

**Veedol SYNTHGLIDE 88 5W-30** meets and exceeds below performances

- API SQ
- ILSAC GF-7A

## Application

- Recommended for latest generation Petrol, CNG and Hybrid vehicles fitted with after treatment devices meeting Euro VI norms.
- Turbocharged GDI engines, supercharged gasoline, multi-valve fuel injected engines found in passenger cars.
- Suitable for use in all modern generation cars such as Toyota, Honda, Suzuki, Hyundai, Kia, Mercedes Benz, BMW, Audi, VW, Fiat, Ford, GM Chrysler etc.

## Typical Properties

PROPERTIES	UNIT	ASTM TEST METHOD	TYPICAL RESULTS
Appearance	-	Visual	Clear & Bright
ASTM Colour	D 1500		L2.5
Density @ 29.5°C	g/cm <sup>3</sup>	D 4052	0.8422
Kinematic Viscosity @ 40°C	cSt	D 445	60.50
Kinematic Viscosity @ 100°C	cSt	D 445	10.14
Viscosity Index		D 2270	155
Total Base Number	mgKOH/g	D 2896	8.81
Pour Point	°C	D 97	-36
Flash Point	°C	D 92	224

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



### STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



### HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

### VEEDOL CORPORATION LIMITED

[Formerly Tide Water Oil Co. (India) Limited]

Corporate Office: 902, Godrej TWO, Vikhroli, Eastern Express Highway, Mumbai-400 079.

Regd. Office: Yule house, 8, Dr. Rajendra Prasad Sarani, Kolkata-700 001, West Bengal, India.

www.veedolindia.com

Rev no.0, Date: 18.09.25