

Veedol SYNTHGLIDE 80 SUV 5W-30 SP/ACEA C2-C3

Boosted Power. Assured Protection

Product Description:

Veedol SYNTHGLIDE 80 SUV 5W-30 is a NextGen fully synthetic passenger car oil powered by EstoBioLide™, a unique bio-inspired technology delivering unmatched lubricity, superior cleanliness, and longer oil life.

Formulated with advanced polymer chemistry, it ensures consistent power delivery, superior wear protection and smooth driving comfort.

Performance Specifications:

Veedol SYNTHGLIDE 80 SUV 5W-30 meets and exceeds below performances

- API SP
- ACEA C2/C3

Application:

- Recommended for latest generation Diesel, Petrol, CNG and Hybrid vehicles fitted with after treatment devices meeting Euro VI norms.
- Turbocharged GDI engines, supercharged gasoline, multi-valve fuel injected engines found in passenger cars, SUVs, light trucks and vans.
- Suitable for use in all modern generation cars such as Toyota, Honda, Suzuki, Hyundai, Kia, Mercedes Benz, BMW, Audi, ISUZU, etc.

Features/Benefits:

- **Absolute Defense:** Formulated with advanced detergency technology, this oil significantly reduces varnish and deposit formation, keeping modern car engines exceptionally clean. The result is smoother operation, sustained efficiency, and longer-lasting engine performance.”
- **Minimize Low-Speed Pre-Ignition:** Proven to reduce Low-Speed Pre-Ignition (LSPI) by up to 48%, this advanced formulation delivers superior protection for modern TGDI and GDI engines.
- **Unmatched Protection:** Engineered with advanced anti-wear chemistry, this oil delivers up to 25% better defense against wear and tear.
- **Fuel Efficiency:** High shear stability ensures optimum lubrication, delivering improved mileage in city and highway riding.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Appearance	-	Visual	Clear & Bright
ASTM Colour		D 1500	L2.5
Density @ 29.5 °C	g/cm ³	D 4052	0.8386
Kinematic Viscosity @ 40°C	cSt	D 445	52.91
Kinematic Viscosity @ 100°C	cSt	D 445	9.515
Viscosity Index		D 2270	166
Total Base Number	mgKOH/g	D 2896	8.15
Pour Point	°C	D 97	-33
Flash Point	°C	D 92	224

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.