

Veedol SYNTRON 5W-40

Fully Synthetic Premium Engine Oil

Product Description:

Veedol Synttron 5W-40 is a high performance fully synthetic premium engine oil formulated with latest lubricant technology system providing unmatched performance in toughest conditions.

Veedol Synttron 5W-40 is a perfect blend of superior quality base oils and latest technology additive system ensuring optimum power, performance, fuel efficiency, protection, durability and lower emissions.

Veedol Synttron 5W-40 is most suitable for all modern generation turbocharged/ supercharged petrol and diesel passenger cars.

Performance Specifications:

Veedol SYNTRON 5W-40 meets and exceeds below performances

- API SN / CF
- ACEA A3/B4-16
- MB 229.3 / 226.5
- VW 502.00 / 505.00
- BMW LL-01
- Porsche A 40
- Renault 710 / 700

Application:

- Recommended for both Petrol and Diesel Engines.
- Turbocharged GDI engines, supercharged gasoline, multi-valve fuel injected engines found in passenger cars, SUV's, light trucks and vans.
- Suitable for use in all modern generation cars such as Toyota, Honda, Suzuki, Hyundai, Kia, Mercedes Benz, BMW, Skoda, Chevrolet, Nissan, Fiat, TATA Motors, etc.

Features/Benefits:

- Excellent piston deposit control property.
- Provides optimum performance and engine protection in harsh condition.
- Superior protection against sludge formation and combustion contamination.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

- Excellent cold temperature property providing cold start requirement.

Typical Properties:

Test Parameters	Unit	ASTM Test Method	Typical results
Appearance	-	Visual	Clear & Bright
Kinematic Viscosity @ 100°C	cSt	D 445	13.9
Viscosity Index		D 2270	169
Total Base Number	mgKOH/g	D 2896	10.5
Pour Point	°C	D 97	-36
Flash Point	°C	D 92	232

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.



STORAGE

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



HEALTH, SAFETY AND ENVIRONMENT

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.