



Lubricants

## SYNTRON 5W-40 API SN/CF

### FULLY SYNTHETIC PREMIUM ENGINE OIL

#### DESCRIPTION

Veedol Syntron 5W-40 is a high performance fully synthetic premium engine oil formulated with latest lubricant technology system providing unmatched performance in toughest conditions.

Veedol Syntron 5W-40 is a perfect blend of superior quality base oils and latest technology additive system ensuring optimum power, performance, fuel efficiency, protection, durability and lower emissions.

Veedol Syntron 5W-40 is most suitable for all modern generation turbocharged/ supercharged petrol and diesel passenger cars.

#### PERFORMANCE SPECIFICATIONS

Meets & Exceeds the performance requirements of

- API SN/CF
- ACEA A3/B4-16
- MB 229.3/226.5
- VW 502.00/505.00
- BMW LL-01
- Opel GM-LL-B-025 level
- Porsche A40
- Renault 710/700

#### APPLICATIONS

Recommended for all new generation cars manufactured by Mercedes Benz, BMW, Skoda, Volkswagen, Chevrolet, Renault, Nissan, Fiat, Tata and Maruti Suzuki.

#### FEATURES/BENEFITS

- Excellent piston deposit control.
- Provides optimum performance and engine protection at all operating temperatures.
- Improved fuel efficiency.
- Superior protection against sludge formation and combustion contamination.
- High level of engine cleanliness.
- Excellent cold temperature properties.

#### CHARACTERISTICS

Test Parameter	Test Method	Typical Value
Kinematic Viscosity @ 100°C, cSt	ASTM D 445	13.9
Viscosity Index	ASTM D 2270	169
Flash Point, (COC) °C	ASTM D 92	232
Pour Point, °C	ASTM D 97	-36
CCS Viscosity @ -20°C, mPa.s	ASTM D 5293	5400