

## SCOOTER GEAR OIL 80W-90

### Heavy-duty Scooter Gear Oil

#### Product Description

Veedol Scooter Gear Oil is a heavy-duty multigrade SAE 80W-90 gear oil meeting API GL-5 performance specification. Veedol Scooter Gear Oil is specially developed for use in gearless scooters and mopeds.

Veedol Scooter Gear Oil is formulated with high performance base oils and special extreme pressure additives which provides protection to gear and its components under frequent start-stop conditions.

#### Performance Specifications:

Veedol Scooter Gear Oil meets & exceeds the performance requirements of

API GL-5

#### Application:

- Recommended for use in all make of gearless scooter and mopeds.

#### Features/Benefits:

- EP additive provides adequate film thickness to the gears and bearings during frequent start-stop running of the scooter.
- Protects the scooter gear from wear operating at high speed/ high load & in hot conditions.
- Excellent low temperature fluidity and foam control
- Excellent thermal and oxidation stability



#### **STORAGE**

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.



#### **HEALTH, SAFETY AND ENVIRONMENT**

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.

**Typical Properties:**

| Test Parameters             | Unit | ASTM Test Method | Typical results |
|-----------------------------|------|------------------|-----------------|
| Kinematic Viscosity @ 100°C | cSt  | D 445            | 14.80           |
| Viscosity Index             |      | D 2270           | 102             |
| Flash Point                 | °C   | D 92             | 242             |
| Pour Point                  | °C   | D 927            | -27             |

The above typical properties are those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

**STORAGE**

All packages should be stored under cover. It should not be exposed to direct sunlight, intense cold and extreme temperature fluctuations. Where outside storage is unavoidable, drums should be laid horizontally or properly covered to avoid the possible ingress of water and damage to drum markings.

**HEALTH, SAFETY AND ENVIRONMENT**

The information on this product is available in the Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information, we recommend you review the MSDS. If handled correctly, there are no special precautions suggested.