



Lubricants

TAKE-OFF 4T ULTRA 5W-30 SN

FULLY SYNTHETIC PREMIUM 4-STROKE MOTORCYCLE ENGINE OIL DESCRIPTION

Veedol Take-Off 4T Ultra 5W-30 SN is fully synthetic BS-VI compliant low viscosity 4-stroke engine oil specifically developed for modern generation motorcycles to support fuel efficiency with less emission and without compromising the engine durability.

Veedol Take-Off 4T Ultra 5W-30 SN is formulated with premium quality synthetic base oils having high viscosity index and specially selected additive system which ensure optimum engine performance under variety of riding conditions.

Veedol Take-Off 4T Ultra 5W-30 SN exhibits effective lubrication as well as protection of engine, gear and transmission system of BS-VI, BS-IV & older generation motorcycles.

PERFORMANCE SPECIFICATIONS

Meets & exceeds performance requirements of

- API SN
- JASO MA2 (T903:2016)

APPLICATIONS

- Recommended for all new generation BS-VI/ Euro-VI compliant motorcycles and other two wheelers.
- Suitable for use in older generation motorcycles.

FEATURES/BENEFITS

- Optimum protection to after treatment devices used in new generation motorcycles meeting BS-VI emission norms.
- Low evaporation loss contributes to less oil consumption.
- Excellent detergency to keep engine clean and enhance engine life.
- Excellent wear protection to engine, gear & clutch even under stop & go conditions.
- High oxidation stability and heat stability.
- Adequate film thickness provides optimum lubrication at high operating temperatures
- JASO MA2 licensed meeting the latest JASO T903:2016 standard.
- Supports fuel efficiency.

CHARACTERISTICS

| Test Parameter | Test Method | Typical Value |
|----------------------------------|-------------|---------------|
| Kinematic Viscosity @ 100°C, cSt | ASTM D 445 | 10.9 |
| Viscosity Index | ASTM D 2270 | 160 |
| Flash Point, (COC) °C | ASTM D 92 | 244 |
| Pour Point, °C | ASTM D 97 | -39 |
| CCS Viscosity @ -20°C, mPa.s | ASTM D 5293 | 6000 |